

BXS SERIES

Feature

- . 100 scale division to show the resistance setting
- . Enclose in robust sheet metal cover
- . Good linearity
- . Sliding contact of coppers graphite

Specifications

- . Max. Working Voltage: 380VAC, 400VDC
- . Resistance tolerance: $\pm 10\%$
- . Insulation resistance: $> 3 \times 10^9 \Omega$
- . Earthing resistance: $< 0.1 \Omega$
- . Rated resistance: see table



BXS 600

Model	Power VA	Resistance (Ω)	Max. Current	Dimensions (W×H×D)	Ceramic Pipe diameter	Weight (kg)
BXS 150	160	10	4A	285×140×95mm	47mm	1.8
		33	2.2A			
		100	1.25A			
		330	0.7A			
		1000	0.4A			
		3300	0.22A			
BXS 300	320	3.3	10A	385×140×95mm	47mm	2.4
		10	5.7A			
		33	3.1A			
		100	1.8A			
		330	1.0A			
		1000	0.57A			
BXS 600	640	3300	0.31A	485×160×100mm	64mm	3.2
		10000	0.18A			
		1.6	20A			
		5	11.4A			
		16.5	6.2A			
		50	3.6A			
BXS 600	640	165	2A	485×160×100mm	64mm	3.2
		500	1.1A			
		1650	0.63A			
		5000	0.36A			