

M10-AD22 SERIES



Features

- .AC and DC combined power supply
- .DC constant voltage and constant current
- .AC output over load protection
- .19-inch rack mount (3U) and benchtop
- .Output from front panel and rear panel
- .Temperature controlled fan



M10-AD2210

Specifications

DC output

- .Line regulation: CV $1 \times 10^{-4} + 3\text{mV}$ CC $2 \times 10^{-3} + 3\text{mA}$
Fixed output 10mV
- .Load regulation: CV $1 \times 10^{-4} + 5\text{mV}$ CC $2 \times 10^{-3} + 5\text{mA}$
Fixed output 10mV
- .Ripple & Noise: CV 1mVrms CC 3mArms
Fixed output 10mV
- .Fixed output accuracy: 2.5%
- .Display accuracy: Voltmeter $\pm(0.2\%Rdg+2\text{digits})$
Ammeter $\pm(1.0\%Rdg+2\text{digits})$

AC output

- .Display accuracy: Voltmeter $\pm(1.0\%Rdg+2\text{digits})$
Ammeter $\pm(1.0\%Rdg+2\text{digits})$
- .Input voltage: 110~127VAC $\pm 10\%$, 220~240VAC $\pm 10\%$ Switchable

Model	DC Output Voltage	DC Output Current	AC Output Voltage	AC Output Current	Size	Weight (kg)
M10-AD2205	0~30V,5V	0~5A,3A	0~250V	2.5A	19" 3U	14
M10-AD2210	0~30V,5V	0~5A,3A	0~250V	4.5A	19" 3U	16